

## LK-POW, BK-POW series

**Pressed steel castors, heavy-duty design,  
with top plate,  
with low noise nylon wheel**



200–220 kg

**Bracket:** LK/BK series

- strong pressed steel, zinc-plated, blue-passivated, Cr6-free

**Swivel bracket:**


- double ball bearing in the swivel head
- swivel head seal
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

**Wheel:** POW series

- high-quality nylon 6, impact resistant, hardness 70 Shore D, colour white
- low-noise operation (-10 decibels) with elastic cushion layer made from elastic solid rubber, colour red

**Additional details:**

- bracket series: page 92
- brakes: page 112–113
- wheel series: page 340
- bearing types: page 84–85



6

Swivel castors	Fixed castors	Swivel castors with "stop-fix" brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
LK-POW 100KF-1	BK-POW 100KF-1	LK-POW 100KF-1-FI	100	35	200	ball bearing (C)	130	100 x 85	80 x 60	9	45
LK-POW 100KF-3	BK-POW 100KF-3	LK-POW 100KF-3-FI	100	35	200	ball bearing (C)	130	140 x 110	105 x 75–80	11	45
LK-POW 125KF-1	BK-POW 125KF-1	LK-POW 125KF-1-FI	125	35	220	ball bearing (C)	155	100 x 85	80 x 60	9	48
LK-POW 125KF-3	BK-POW 125KF-3	LK-POW 125KF-3-FI	125	35	220	ball bearing (C)	155	140 x 110	105 x 75–80	11	48

### Versions / options



	directional lock (separate) 1 x 360°	directional lock (separate) 1 x 360°
Technical description page	115	115
<b>Product code suffix</b>	<b>RI-05.01</b>	<b>RI-03.03</b>
Available for	all with plate 100x85 mm *	all with plate 140x110 mm *

\* Only for swivel castors without brake