

ALEV, ALST, ALTH, PO series

Front wheels for pallet trucks

500–800 kg



Wheel: ALEV series

- tyre: high-quality elastic solid rubber “Blickle EasyRoll” in smooth rolling quality, hardness 65 Shore A, colour black
- wheel centre: die-cast aluminium
- overview wheel series page 63

Wheel: ALST series

- tread: high-quality polyurethane elastomer Blickle Softhane®, hardness 75 Shore A, colour green, non-marking, non-staining
- wheel centre: die-cast aluminium
- overview wheel series page 66

Wheel: ALTH series

- tread: high-quality polyurethane elastomer Blickle Extrathane®, hardness 92 Shore A, colour light brown, non-marking, non-staining
- wheel centre: die-cast aluminium
- overview wheel series page 65

Wheel: PO series

- high-quality nylon 6, impact resistant, hardness 70 Shore D, colour natural white
- overview wheel series page 69

Wheels	Wheel Ø (D) [mm]	Wheel width (T2) [mm]	Load capacity at 4 km/h [kg]	Load capacity at 10 km/h [kg]	Bearing type	Axle bore Ø (d) [mm]	Hub length (T1) [mm]	Clamping length (T5) [mm]
ALEV series								
ALEV 200x50/20-54K	200	50	500	250	ball bearing	20	60	54
ALEV 200x50/25-50K	200	50	500	250	ball bearing	25	60	50
ALST series								
ALST 200x50/20-54K	200	50	700	300	ball bearing	20	60	54
ALST 200x50/25-50K	200	50	700	300	ball bearing	25	60	50
ALTH series								
ALTH 180x50/20-54K	180	50	700	350	ball bearing	20	60	54
ALTH 180x50/25-50K	180	50	700	350	ball bearing	25	60	50
ALTH 200x50/20-40K	200	50	800	400	ball bearing	20	50	40
ALTH 200x50/20-54K	200	50	800	400	ball bearing	20	60	54
ALTH 200x50/25-36K	200	50	800	400	ball bearing	25	50	36
ALTH 200x50/25-50K	200	50	800	400	ball bearing	25	60	50
PO series								
PO 200x50/20-54K	200	50	600	–	ball bearing	20	60	54
PO 200x50/25-50K	200	50	600	–	ball bearing	25	60	50

Versions / options



with stainless steel ball bearing in the wheel hub

Technical description page	84
Product code suffix	-XK
Available for	upon request

